



S150/L_____

ALL SS CHANNELS ARE CUSTOM FABRICATED. ORDERS ARE NON-CANCELLABLE AND NON-RETURNABLE





STANDARD SIZES AND PRODUCT FEATURES

SECTION

OUTLET

OPTIONS (MARK THE FIELD)

SPECIFY DIMENSIONS



☐ OPTIONAL FLAT BOTTOM
(H2 MAX = 95mm)



ANCHOR TABS

LEVELING FEET

FLANGE CONNECTIONS

SPACERS

STAINLESS STEEL FABRICATED STANDARD CHANNEL S150, 150 mm WIDE, OPENING 110 mm WIDE, MATERIAL 2.0 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD), WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE. RUN LENGTHS LONGER THAN 4.0 m PROVIDED WITH FLANGES AND GASKETS.



NOTES

☐ 304

☐ 316L


☐ None

☐ Rubber

☐ Epoxy

☐ Profile

☐ Flat Bar



Mesh Anti-Slip

Perforated

Ladder

Plate

COMPANY

L1 - CENTER / END OUTLET / DISTANCE [mm]

APPROVED BY

DATE

SIGNATURE



S150_OC_Wm-110H2