



STANDARD SIZES AND PRODUCT FEATURES				OPTIONS (MARK THE FIELD)				SPECIFY DIMENSIONS			
SECTION		OUTLET		GRATING		No	L [mm]	L1 [mm]	H1 [mm]	Slope [%]	H2 [mm]
								1	1000		
								2	1500		
								3	2000		
								4	3000		
								5			
L1 - CENTER / END OUTLET / DISTANCE [mm]											
COMPANY											
APPROVED BY											
DATE											
MATERIALS											
<div><div><input type="checkbox"/> None</div><div><input type="checkbox"/> Rubber</div><div><input type="checkbox"/> Epoxy</div><div><input type="checkbox"/> Profile</div><div><input type="checkbox"/> Flat Bar</div></div>											
ANCHOR TABS											
LEVELING FEET											
FLANGE CONNECTIONS											
SPACERS											
<div>STAINLESS STEEL FABRICATED STANDARD CHANNEL S60, 60 mm WIDE, OPENING 20 mm WIDE, MATERIAL 1,5 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD), WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE. RUN LENGTHS LONGER THAN 3,0 m PROVIDED WITH FLANGES AND GASKETS.</div>											
NOTES				<div><div><input type="checkbox"/> 304</div><div><input type="checkbox"/> 316L</div></div>							
SIGNATURE											
ATT INDEX DRAIN											

S60_OC_W200-110H2