


S60/L_____

ALL SS CHANNELS ARE CUSTOM FABRICATED. ORDERS ARE NON-CANCELLABLE AND NON-RETURNABLE



STANDARD SIZES AND PRODUCT FEATURES			OPTIONS (MARK THE FIELD)				SPECIFY DIMENSIONS							
SECTION	OUTLET		GRATING				No	L[mm]	L1[mm]	H1[mm]	Slope[%]	H2[mm]		
							1	1000						
			<input type="checkbox"/> Mesh Anti-Slip	<input type="checkbox"/> Perforated	<input type="checkbox"/> Ladder	<input type="checkbox"/> Plate	2	1500						
							3	2000						
							4	3000						
							5							
			BACKFILL				L1 - CENTER / END OUTLET / DISTANCE [mm]							
							COMPANY							
							APPROVED BY							
							DATE							
ANCHOR TABS			LEVELING FEET				FLANGE CONNECTIONS				SPACERS			
STAINLESS STEEL FABRICATED STANDARD CHANNEL S60, 60 mm WIDE, OPENING 20 mm WIDE, MATERIAL 1,5 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD), WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE, RUN LENGTHS LONGER THAN 3,0 m PROVIDED WITH FLANGES AND GASKETS.														

☐ 304 ☐ 316L

NOTES



S60_OK_Wm-110V2