











ALL SS CHANNELS ARE CUSTOM FABRICATED. ORDERS ARE NON-CANCELLABLE AND NON-RETURNABLE








OPTIONS (MARK THE FIELD)

GRATING				No	L1[mm]	L2[mm]	H1[mm]	Slope[%]	H2[mm]
	<input type="checkbox"/>		<input type="checkbox"/>	1	1000				
	<input type="checkbox"/>		<input type="checkbox"/>	2	1500				
	<input type="checkbox"/>		<input type="checkbox"/>	3	2000				
	<input type="checkbox"/>		<input type="checkbox"/>	4	3000				
	<input type="checkbox"/>		<input type="checkbox"/>	5					

BACKFILL	L1 - CENTER / END OUTLET / DISTANCE [mm]
----------	--

[illegible]

APPROVED BY	
	
	
	
	



<div> <div> <input type="checkbox"/> None </div> <div> <input type="checkbox"/> Rubber </div> <div> <input type="checkbox"/> Epoxy </div> <div> <input type="checkbox"/> Profile </div> <div> <input type="checkbox"/> Flat Bar </div> </div> <div> <div>MATERIALS</div> <div>DATE</div> </div>	

☐ 304 ☐ 316L

SIGNATURE _____

NOTES	


ATT INOX DRAIN



ANCHOR TABS	LEVELING FEET	FLANGE CONNECTIONS	SPACERS
-------------	---------------	--------------------	---------

STAINLESS STEEL FABRICATED STANDARD CHANNEL S60, 60 mm WIDE, OPENING 20 mm WIDE, MATERIAL 1,5 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD) , WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE. RUN LENGTHS LONGER THAN 3,0 m PROVIDED WITH FLANGES AND GASKETS.

STAINLESS STEEL FABRICATED STANDARD CHANNEL S60, 60 mm WIDE, OPENING 20 mm WIDE, MATERIAL 1,5 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD), WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE. RUN LENGTHS LONGER THAN 3,0 m PROVIDED WITH CHANGES AND GASKETS



S60-OC-W200-110H1