



STANDARD SIZES AND PRODUCT FEATURES				OPTIONS (MARK THE FIELD)				SPECIFY DIMENSIONS											
SECTION		OUTLET		GRATING				No	L [mm]	L1 [mm]	H1 [mm]	Slope [%]	H2 [mm]						
								1	1000										
								2	1500										
								3	2000										
								4	3000										
								5											
L1 - CENTER / END OUTLET / DISTANCE [mm]																			
COMPANY																			
APPROVED BY																			
DATE																			
MATERIALS																			
<input type="checkbox"/> None				<input type="checkbox"/> Rubber				<input type="checkbox"/> Epoxy				<input type="checkbox"/> Profile				<input type="checkbox"/> Flat Bar			
ANCHOR TABS				LEVELING FEET				FLANGE CONNECTIONS				SPACERS							
STAINLESS STEEL FABRICATED STANDARD CHANNEL S60, 60 mm WIDE, OPENING 20 mm WIDE, MATERIAL 1.5 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD), WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE, RUN LENGTHS LONGER THAN 3.0 m PROVIDED WITH FLANGES AND GASKETS.																			

ATT Sp. z o.o. ul. Rybitwy 15, 30-722 Kraków, Poland tel: +48 12 290 29 30 fax: +48 290 29 31, e-mail: att@att.eu, www.att.eu

ATT INDEX DRAIN

S60\_OK\_W200-110V1