


S150/L\_\_\_\_\_

ALL SS CHANNELS ARE CUSTOM FABRICATED. ORDERS ARE NON-CANCELLABLE AND NON-RETURNABLE



STANDARD SIZES AND PRODUCT FEATURES				OPTIONS (MARK THE FIELD)				SPECIFY DIMENSIONS					
SECTION		OUTLET		GRATING				No	L [mm]	L1 [mm]	H1 [mm]	Slope [%]	H2 [mm]
								1	1000				
				<input type="checkbox"/> Mesh Anti-Slip	<input type="checkbox"/> Perforated	<input type="checkbox"/> Ladder	<input type="checkbox"/> Plate	2	1500				
				BACKFILL				3	2000				
				<input type="checkbox"/> 4	3000								
ANCHOR TABS		LEVELING FEET		FLANGE CONNECTIONS		SPACERS		MATERIALS		NOTES		SIGNATURE	
		<input type="checkbox"/> OPTIONAL FLAT BOTTOM (H2 MAX = 95mm)						<input type="checkbox"/> None <input type="checkbox"/> Rubber <input type="checkbox"/> Epoxy <input type="checkbox"/> Profile <input type="checkbox"/> Flat Bar		<input type="checkbox"/> 304 <input type="checkbox"/> 316L			
STAINLESS STEEL FABRICATED STANDARD CHANNEL S150, 150 mm WIDE, OPENING 110 mm WIDE, MATERIAL 2.0 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD), WITH ANCHOR TABS AND LEVELING FEET. DIFFERENT OUTLET GRATING'S AVAILABLE. RUN LENGTHS LONGER THAN 4.0 m PROVIDED WITH FLANGES AND GASKETS.													

S150\_OC\_W200-110V1