



STANDARD SIZES AND PRODUCT FEATURES				OPTIONS (MARK THE FIELD)				SPECIFY DIMENSIONS					
SECTION		OUTLET		GRATING				No	L [mm]	L1 [mm]	H1 [mm]	Slope [%]	H2 [mm]
								1	1000				
								2	1500				
								3	2000				
								4	3000				
								5					
				BACKFILL				L1 - CENTER / END OUTLET / DISTANCE [mm]					
				<input type="checkbox"/> Mesh Anti-Slip <input type="checkbox"/> Perforated <input type="checkbox"/> Ladder <input type="checkbox"/> Plate				COMPANY					
								APPROVED BY					
				<input type="checkbox"/> None <input type="checkbox"/> Rubber <input type="checkbox"/> Epoxy <input type="checkbox"/> Profile <input type="checkbox"/> Flat Bar				DATE					
ANCHOR TABS				LEVELING FEET		FLANGE CONNECTIONS		SPACERS		MATERIALS			
				STAINLESS STEEL FABRICATED STANDARD CHANNEL S60, 60 mm WIDE, OPENING 20 mm WIDE, MATERIAL 1,5 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD), WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE, RUN LENGTHS LONGER THAN 3,0 m PROVIDED WITH FLANGES AND GASKETS.				<input type="checkbox"/> 304 <input type="checkbox"/> 316L				SIGNATURE	
								NOTES					