


S60/L\_\_\_\_\_

ALL SS CHANNELS ARE CUSTOM FABRICATED. ORDERS ARE NON-CANCELLABLE AND NON-RETURNABLE



STANDARD SIZES AND PRODUCT FEATURES				OPTIONS (MARK THE FIELD)				SPECIFY DIMENSIONS					
SECTION		OUTLET		GRATING				No	L [mm]	L 1 [mm]	H1 [mm]	Slope [%]	H2 [mm]
								1	1000				
								2	1500				
								3	2000				
								4	3000				
								5					
L1 - CENTER / END OUTLET / DISTANCE [mm]													
COMPANY													
APPROVED BY													
DATE													
MATERIALS													
<input type="checkbox"/> None <input type="checkbox"/> Rubber <input type="checkbox"/> Epoxy <input type="checkbox"/> Profile <input type="checkbox"/> Flat Bar													
NOTES				<input type="checkbox"/> 304 <input type="checkbox"/> 316L									
ANCHOR TABS				LEVELING FEET				FLANGE CONNECTIONS					
STAINLESS STEEL FABRICATED STANDARD CHANNEL S60, 60 mm WIDE, OPENING 20 mm WIDE, MATERIAL 1,5 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD), WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE. RUN LENGTHS LONGER THAN 3,0 m PROVIDED WITH FLANGES AND GASKETS.													

ATT SP. z o.o. ul. Rybitwy 15, 30-722 Kraków, Poland tel: +48 12 290 29 30 fax: +48 290 29 31, e-mail: att@att.eu, www.att.eu

S60\_OK\_Wm-110H1