


S200/L

ALL SS CHANNELS ARE CUSTOM FABRICATED. ORDERS ARE NON-CANCELLABLE AND NON-RETURNABLE



STANDARD SIZES AND PRODUCT FEATURES

OPTIONS (MARK THE FIELD)

SPECIFY DIMENSIONS

SECTION		OUTLET		GRATING				No	L[mm]	L1[mm]	H1[mm]	Slope[%]	H2[mm]
								1	1000				
				<input type="checkbox"/> Mesh Anti-Slip	<input type="checkbox"/> Perforated	<input type="checkbox"/> Ladder	<input type="checkbox"/> Plate	2	1500				
								3	2000				
								4	3000				
								5					
				BACKFILL				L1 - CENTER / END OUTLET / DISTANCE [mm]					
									COMPANY				
				<input type="checkbox"/> None	<input type="checkbox"/> Rubber	<input type="checkbox"/> Epoxy	<input type="checkbox"/> Profile	<input type="checkbox"/> Flat Bar	APPROVED BY				
									DATE				
									SIGNATURE				
ANCHOR TABS		LEVELING FEET		FLANGE CONNECTIONS		SPACERS		MATERIALS					
								<input type="checkbox"/> 304 <input type="checkbox"/> 316L					
		<p>STAINLESS STEEL FABRICATED STANDARD CHANNEL S200, 200 mm WIDE, OPENING 160 mm WIDE, MATERIAL 2,0 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD) , WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE. RUN LENGTHS LONGER THAN 4,0 m PROVIDED WITH FLANGES AND GASKETS.</p>						NOTES					

S200_OC_W200-110H2

S200_OC_W200-110H2