S60/L_____

ALL SS CHANNELS ARE CUSTOM FABRICATED. ORDERS ARE NON-CANCELLABLE AND NON-RETURNABLE



STANDARD SIZES AND PRODUCT FEATURES

SECTION



OUTLET



ANCHOR TABS



LEVELING FEET

FLANGE CONNECTIONS

SPACERS



STAINLESS STEEL FABRICATED STANDARD CHANNEL S60, 60 mm WIDE , OPENING 20 mm WIDE , MATERIAL 1,5 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD) , WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING`S AVAILABLE. RUN LENGTHS LONGER THAN 3,0 m PROVIDED WITH FLANGES AND GASKETS.

OPTIONS (MARK THE FIELD)

GRATING



☐ Mesh Anti-Slip ☐ Perforated ☐ Ladder ☐ Plate

BACKFILL



☐ None ☐ Rubber ☐ Epoxy ☐ Profile ☐ Flat Bar

MATERIALS

☐ 304 ☐ 316L

NOTES

SPECIFY DIMENSIONS

No	L[mm]	L1[mm]	H1[mm]	Slope[%]	H2[mm]
1	1000				
2	1500				
3	2000				
4	3000				
5					

L1 - CENTER / END OUTLET / DISTANCE [mm]

COMPANY

APPROVED BY

DATE

SIGNATURE

ATT INOX DRAIN®

S60_OK_Wm-110H2

ATT Sp. z o.o. ul. Rybitwy 15, 30-722 Kraków, Poland tel: +48 12 290 29 30 fax: +48 290 29 31, e-mail: att@att.eu, www.att.eu