


S60/L_____

ALL SS CHANNELS ARE CUSTOM FABRICATED. ORDERS ARE NON-CANCELLABLE AND NON-RETURNABLE



STANDARD SIZES AND PRODUCT FEATURES

SECTION		OUTLET		OPTIONS (MARK THE FIELD)					SPECIFY DIMENSIONS								
				GRATING					No	L1[mm]	L2[mm]	H1[mm]	Slope[%]	H2[mm]			
					<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>	1	1000				
					<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>	2	1500				
					<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>	3	2000				
					<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>	4	3000				
					<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>	5					
				BACKFILL					L1 - CENTER / END OUTLET / DISTANCE [mm]								
									COMPANY								
									APPROVED BY								
									DATE								
ANCHOR TABS		LEVELING FEET		FLANGE CONNECTIONS		SPACERS		MATERIALS					SIGNATURE				
								<input type="checkbox"/> 304 <input type="checkbox"/> 316L									
STAINLESS STEEL FABRICATED STANDARD CHANNEL S60, 60 mm WIDE, OPENING 20 mm WIDE, MATERIAL 1.5 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD), WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE, RUN LENGTHS LONGER THAN 3.0 m PROVIDED WITH FLANGES AND GASKETS.													S60_OC_W200-110V2				