



STANDARD SIZES AND PRODUCT FEATURES				OPTIONS (MARK THE FIELD)				SPECIFY DIMENSIONS					
SECTION		OUTLET		GRATING				No	L1[mm]	L2[mm]	H1[mm]	Slope[%]	H2[mm]
								1	1000				
								2	1500				
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	3	2000				
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	4	3000				
				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	5					
				L1 - CENTER / END OUTLET / DISTANCE [mm]									
				COMPANY									
				APPROVED BY									
				DATE									
ANCHOR TABS		LEVELING FEET		FLANGE CONNECTIONS		SPACERS		MATERIALS					
								<input type="checkbox"/> 304	<input type="checkbox"/> 316L				
<p>STAINLESS STEEL FABRICATED STANDARD CHANNEL S60, 60 mm WIDE, OPENING 20 mm WIDE, MATERIAL 1,5 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD), WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE. RUN LENGTHS LONGER THAN 3,0 m PROVIDED WITH FLANGES AND GASKETS.</p>								NOTES					
								SIGNATURE					