


S200/L

ALL SS CHANNELS ARE CUSTOM FABRICATED. ORDERS ARE NON-CANCELLABLE AND NON-RETURNABLE



## STANDARD SIZES AND PRODUCT FEATURES

## OPTIONS (MARK THE FIELD)

## SPECIFY DIMENSIONS

## SECTION

## OUTLET

## GRATING

## No







## L[mm]

## L1[mm]

## H1[mm]

## Slope[%]

## H2[mm]


☐ Mesh Anti-Slip

☐ Perforated

☐ Ladder

☐ Plate

1

1000

2

1500

3

2000






4

3000

5

## BACKFILL

## L1 - CENTER / END OUTLET / DISTANCE [mm]


☐ None

☐ Rubber

☐ Epoxy

☐ Profile

☐ Flat Bar

COMPANY

APPROVED BY

DATE

SIGNATURE

## ANCHOR TABS


## LEVELING FEET

## FLANGE CONNECTIONS

## SPACERS

## MATERIALS

STAINLESS STEEL FABRICATED STANDARD CHANNEL S200, 200 mm WIDE, OPENING 160 mm WIDE, MATERIAL 2,0 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE ( 1% STANDARD ), WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE. RUN LENGTHS LONGER THAN 4,0m PROVIDED WITH FLANGES AND GASKETS.


☐ 304

☐ 316L

## NOTES

S200\_OC\_Wm-110V1