



STANDARD SIZES AND PRODUCT FEATURES				OPTIONS (MARK THE FIELD)				SPECIFY DIMENSIONS					
SECTION		OUTLET		GRATING				No	L [mm]	L1 [mm]	H1 [mm]	Slope [%]	H2 [mm]
								1	1000				
								2	1500				
								3	2000				
								4	3000				
								5					
				BACKFILL				L1 - CENTER / END OUTLET / DISTANCE [mm]					
				<input type="checkbox"/> Mesh Anti-Slip <input type="checkbox"/> Perforated <input type="checkbox"/> Ladder <input type="checkbox"/> Plate				COMPANY					
								APPROVED BY					
				<input type="checkbox"/> None <input type="checkbox"/> Rubber <input type="checkbox"/> Epoxy <input type="checkbox"/> Profile <input type="checkbox"/> Flat Bar				DATE					
ANCHOR TABS				LEVELING FEET		FLANGE CONNECTIONS		SPACERS		MATERIALS			
										<input type="checkbox"/> 304 <input type="checkbox"/> 316L			
STAINLESS STEEL FABRICATED STANDARD CHANNEL S60, 60 mm WIDE, OPENING 20 mm WIDE, MATERIAL 1,5 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD), WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE. RUN LENGTHS LONGER THAN 3,0 m PROVIDED WITH FLANGES AND GASKETS.										NOTES			
										SIGNATURE			

