


S200/L\_\_\_\_\_

ALL SS CHANNELS ARE CUSTOM FABRICATED. ORDERS ARE NON-CANCELLABLE AND NON-RETURNABLE



## STANDARD SIZES AND PRODUCT FEATURES

## OPTIONS (MARK THE FIELD)

## SPECIFY DIMENSIONS

SECTION		OUTLET	GRATING				No	L[mm]	L1[mm]	H1[mm]	Slope[%]	H2[mm]
							1	1000				
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	2	1500				
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	3	2000				
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	4	3000				
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	5					
			BACKFILL					L1 - CENTER / END OUTLET / DISTANCE [mm]				
								COMPANY				
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	APPROVED BY				
								DATE				
								SIGNATURE				
ANCHOR TABS 		LEVELING FEET STAINLESS STEEL FABRICATED STANDARD CHANNEL S200, 200 mm WIDE, OPENING 160 mm WIDE, MATERIAL 2,0 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE ( 1% STANDARD ) , WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE. RUN LENGTHS LONGER THAN 4,0 m PROVIDED WITH FLANGES AND GASKETS.	FLANGE CONNECTIONS 		SPACERS 		MATERIALS <input type="checkbox"/> 304 <input type="checkbox"/> 316L					
						NOTES						

S200\_OK\_W200-110H1