


S200/L_____

ALL SS CHANNELS ARE CUSTOM FABRICATED. ORDERS ARE NON-CANCELLABLE AND NON-RETURNABLE



STANDARD SIZES AND PRODUCT FEATURES

OPTIONS (MARK THE FIELD)

SPECIFY DIMENSIONS

SECTION		OUTLET	GRATING				No	L[mm]	L1[mm]	H1[mm]	Slope[%]	H2[mm]	
							1	1000					
			<input type="checkbox"/> Mesh Anti-Slip	<input type="checkbox"/> Perforated	<input type="checkbox"/> Ladder	<input type="checkbox"/> Plate	2	1500					
							3	2000					
							4	3000					
							5						
<input type="checkbox"/> OPTIONAL FLAT BOTTOM (H2 MAX = 100 mm)			BACKFILL				L1 - CENTER / END OUTLET / DISTANCE [mm]						
								COMPANY _____					
			<input type="checkbox"/> None	<input type="checkbox"/> Rubber	<input type="checkbox"/> Epoxy	<input type="checkbox"/> Profile	<input type="checkbox"/> Flat Bar	APPROVED BY _____					
ANCHOR TABS		LEVELING FEET	FLANGE CONNECTIONS	SPACERS	MATERIALS		DATE _____						
		STAINLESS STEEL FABRICATED STANDARD CHANNEL S200, 200 mm WIDE, OPENING 160 mm WIDE, MATERIAL 2,0 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD), WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE. RUN LENGTHS LONGER THAN 4,0 m PROVIDED WITH FLANGES AND GASKETS.			<input type="checkbox"/> 304 <input type="checkbox"/> 316L		SIGNATURE _____						
					NOTES _____								

S200_OK_Wm-110H1