


S200/L\_\_\_\_\_

*ALL SS CHANNELS ARE CUSTOM FABRICATED. ORDERS ARE NON-CANCELLABLE AND NON-RETURNABLE*



## STANDARD SIZES AND PRODUCT FEATURES

**OPTIONS (MARK THE FIELD)**

**SPECIFY DIMENSIONS**

SECTION		OUTLET	GRATING				No	L[mm]	L1[mm]	H1[mm]	Slope[%]	H2[mm]
							1	1000				
			<input type="checkbox"/> Mesh Anti-Slip	<input type="checkbox"/> Perforated	<input type="checkbox"/> Ladder	<input type="checkbox"/> Plate	2	1500				
							3	2000				
							4	3000				
							5					
<input type="checkbox"/> OPTIONAL FLAT BOTTOM ( H2 MAX = 100 mm )			BACKFILL				L1 - CENTER / END OUTLET / DISTANCE [mm]					
ANCHOR TABS		LEVELING FEET	FLANGE CONNECTIONS	SPACERS	MATERIALS			COMPANY				
		STAINLESS STEEL FABRICATED STANDARD CHANNEL S200, 200 mm WIDE , OPENING 160 mm WIDE , MATERIAL 2,0 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE ( 1% STANDARD ) , WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE. RUN LENGTHS LONGER THAN 4,0 m PROVIDED WITH FLANGES AND GASKETS.			<input type="checkbox"/> 304 <input type="checkbox"/> 316L			APPROVED BY				
					NOTES			DATE				
								SIGNATURE				

S200\_OK\_W200-110V2

S200\_OK\_W200-110V2