



STANDARD SIZES AND PRODUCT FEATURES				OPTIONS (MARK THE FIELD)				SPECIFY DIMENSIONS					
SECTION		OUTLET		GRATING				No	L [mm]	L1 [mm]	H1 [mm]	Slope [%]	H2 [mm]
150								1	1000				
								2	1500				
								3	2000				
								4	3000				
								5					
								L1 - CENTER / END OUTLET / DISTANCE [mm]					
								COMPANY					
								APPROVED BY					
								DATE					
								SIGNATURE					
								NOTES					
								MATERIALS					
								None <input type="checkbox"/> 304 <input type="checkbox"/> 316L					
								BACKFILL					
								None <input type="checkbox"/> Rubber <input type="checkbox"/> Epoxy <input type="checkbox"/> Profile <input type="checkbox"/> Flat Bar <input type="checkbox"/>					
								ANCHOR TABS					
								LEVELING FEET					
								FLANGE CONNECTIONS					
								SPACERS					
								STAINLESS STEEL FABRICATED STANDARD CHANNEL S150, 150 mm WIDE, OPENING 110 mm WIDE, MATERIAL 2.0 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD), WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE. RUN LENGTHS LONGER THAN 4.0 m PROVIDED WITH FLANGES AND GASKETS.					

