



STANDARD SIZES AND PRODUCT FEATURES				OPTIONS (MARK THE FIELD)				SPECIFY DIMENSIONS					
SECTION		OUTLET		GRATING				No	L [mm]	L1 [mm]	H1 [mm]	Slope [%]	H2 [mm]
								1	1000				
				<input type="checkbox"/> Mesh Anti-Slip	<input type="checkbox"/> Perforated	<input type="checkbox"/> Ladder	<input type="checkbox"/> Plate	2	1500				
								3	2000				
								4	3000				
								5					
L1 - CENTER / END OUTLET / DISTANCE [mm]													
COMPANY													
APPROVED BY													
DATE													
SIGNATURE													
ANCHOR TABS		LEVELING FEET		FLANGE CONNECTIONS		SPACERS		MATERIALS		NOTES			
								<input type="checkbox"/> 304 <input type="checkbox"/> 316L					
STAINLESS STEEL FABRICATED STANDARD CHANNEL S60, 60 mm WIDE, OPENING 20 mm WIDE, MATERIAL 1,5 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD), WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE. RUN LENGTHS LONGER THAN 3,0 m PROVIDED WITH FLANGES AND GASKETS.													

