


S200/L_____

ALL SS CHANNELS ARE CUSTOM FABRICATED. ORDERS ARE NON-CANCELLABLE AND NON-RETURNABLE



STANDARD SIZES AND PRODUCT FEATURES

OPTIONS (MARK THE FIELD)

SPECIFY DIMENSIONS

SECTION

OUTLET

GRATING

No




L[mm]

L1[mm]

H1[mm]

Slope[%]


H2[mm]



1	1000				
2	1500				
3	2000				
4	3000				
5					

BACKFILL

L1 - CENTER / END OUTLET / DISTANCE [mm]



COMPANY					
APPROVED BY					
DATE					
SIGNATURE					



☐ OPTIONAL FLAT BOTTOM
(H2 MAX = 100 mm)

ANCHOR TABS


LEVELING FEET

FLANGE CONNECTIONS

SPACERS

MATERIALS

STAINLESS STEEL FABRICATED STANDARD CHANNEL S200, 200 mm WIDE, OPENING 160 mm WIDE, MATERIAL 2,0 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD), WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE. RUN LENGTHS LONGER THAN 4,0 m PROVIDED WITH FLANGES AND GASKETS.

☐ 304☐ 316L

NOTES

SIGNATURE


ATT INOX DRAIN

S200_OK_Wm-110V1