


S200/L



ALL SS CHANNELS ARE CUSTOM FABRICATED. ORDERS ARE NON-CANCELLABLE AND NON-RETURNABLE



STANDARD SIZES AND PRODUCT FEATURES

SECTION

OUTLET



OPTIONAL FLAT BOTTOM
(H2 MAX = 100 mm)


ANCHOR TABS

LEVELING FEET

FLANGE CONNECTIONS


SPACERS

STAINLESS STEEL FABRICATED STANDARD CHANNEL S200, 200 mm WIDE, OPENING 160 mm WIDE, MATERIAL 2,0 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD) , WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE. RUN LENGTHS LONGER THAN 4,0 m PROVIDED WITH FLANGES AND GASKETS.



OPTIONS (MARK THE FIELD)

GRATING




☐ Mesh Anti-Slip

☐ Perforated

☐ Ladder

☐ Plate

BACKFILL



☐ None

☐ Rubber

☐ Epoxy

☐ Profile

☐ Flat Bar

MATERIALS

☐ 304

☐ 316L

NOTES

SPECIFY DIMENSIONS

No

L[mm]

L1[mm]

H1[mm]

Slope[%]

H2[mm]

1

1000

2

1500

3

2000

4

3000

5

L1 - CENTER / END OUTLET / DISTANCE [mm]

COMPANY

APPROVED BY

DATE

SIGNATURE

ATT INOX DRAIN®

S200_OC_W200-110H1