


S150/L_____

ALL SS CHANNELS ARE CUSTOM FABRICATED. ORDERS ARE NON-CANCELLABLE AND NON-RETURNABLE



STANDARD SIZES AND PRODUCT FEATURES				OPTIONS (MARK THE FIELD)				SPECIFY DIMENSIONS						
SECTION		OUTLET		GRATING				No	L[mm]	L1[mm]	H1[mm]	Slope[%]	H2[mm]	
								1	1000					
				<input type="checkbox"/> Mesh Anti-Slip	<input type="checkbox"/> Perforated	<input type="checkbox"/> Ladder	<input type="checkbox"/> Plate	2	1500					
				BACKFILL				3	2000					
<input type="checkbox"/> OPTIONAL FLAT BOTTOM (H2 MAX = 95mm)				<input type="checkbox"/> None	<input type="checkbox"/> Rubber	<input type="checkbox"/> Epoxy	<input type="checkbox"/> Profile	<input type="checkbox"/> Flat Bar	4	3000				
ANCHOR TABS		LEVELING FEET		FLANGE CONNECTIONS		SPACERS		MATERIALS						
								<input type="checkbox"/> 304 <input type="checkbox"/> 316L						
STAINLESS STEEL FABRICATED STANDARD CHANNEL S150, 150 mm WIDE, OPENING 110 mm WIDE, MATERIAL 2.0 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD), WITH ANCHOR TABS AND LEVELING FEET. DIFFERENT OUTLET GRATING'S AVAILABLE. RUN LENGTHS LONGER THAN 4.0 m PROVIDED WITH FLANGES AND GASKETS.								NOTES						
								DATE						
								SIGNATURE						
								APPROVED BY						
								COMPANY						
								L1 - CENTER / END OUTLET / DISTANCE [mm]						
								5						



S150_OK_W200-110V2