


S200/L_____

ALL SS CHANNELS ARE CUSTOM FABRICATED. ORDERS ARE NON-CANCELLABLE AND NON-RETURNABLE



STANDARD SIZES AND PRODUCT FEATURES

OPTIONS (MARK THE FIELD)

SPECIFY DIMENSIONS

SECTION		OUTLET	GRATING				No	L[mm]	L1[mm]	H1[mm]	Slope[%]	H2[mm]
							1	1000				
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	2	1500				
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	3	2000				
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	4	3000				
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	5					
			BACKFILL					L1 - CENTER / END OUTLET / DISTANCE [mm]				
								COMPANY				
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	APPROVED BY				
								DATE				
								SIGNATURE				
ANCHOR TABS 		LEVELING FEET STAINLESS STEEL FABRICATED STANDARD CHANNEL S200, 200 mm WIDE, OPENING 160 mm WIDE, MATERIAL 2,0 mm THICK, AVAILABLE WITH OR WITHOUT SLOPE (1% STANDARD) , WITH ANCHOR TABS AND LEVELING FEET, DIFFERENT OUTLET GRATING'S AVAILABLE. RUN LENGTHS LONGER THAN 4,0 m PROVIDED WITH FLANGES AND GASKETS.	FLANGE CONNECTIONS 		SPACERS 		MATERIALS <input type="checkbox"/> 304 <input type="checkbox"/> 316L		NOTES			

S200_OC_W200-110V2